

PMD (UK) LTD PROCESS DATA

PMD (UK) Ltd, Broad Lane, Coventry, CV5 7AY, England. Telephone 024 7646 6691 Fax 024 7647 3034
Web Site: www.pmdgroup.co.uk Email: sales@pmdgroup.co.uk

MFS1255-01/03
ISSUE 2
PREV 1195-1

MFS 1255 **HORIZONTAL HASL FLUX**

INTRODUCTION

MFS 1255 Horizontal HASL Flux is a heat stable organic flux used in horizontal hot air levelling.

It is water soluble, non-foaming and is easily removed by rinsing the printed circuit boards in water.

BENEFITS

First time coverage of difficult SMD pads.

High SIR-values.

Water soluble.

Non foaming.

SOLUTION CHARACTERISTICS

Specific gravity (25°C)	1.07g/cm ³
Viscosity (25°C)	11cps
Flash point (COC)	315°C

EQUIPMENT

Can be used in dip or roller applications.

INSTALLATION

It is essential that the tanks to be used for MFS 1255 Horizontal HASL Flux are thoroughly cleaned before any chemistry is introduced.

Contact PMD (UK) Limited Technical Department for appropriate procedure.

**MFS1255-01/03
ISSUE 2**

PROCESS SEQUENCE

1. Microetch in Procirc 921, 923 or SP263 Microetch.
2. Rinse.
3. Dry (Preferable).
4. MFS 1255 Horizontal HASL Flux application (roller or dip).
5. Solder level.
6. Wash off.
7. Dry.

MAINTENANCE AND CONTROL

Under optimum processing conditions it is not necessary to carry out analytical maintenance and control in order to maintain the performance of this product.

DISPOSAL

Dispose of in accordance with Local Authority requirements.

PRODUCT FAMILIES

The following products are referred to in this Data Sheet.

<u>Product Name</u>	<u>Product Number</u>
MFS 1255 Horizontal HASL Flux	997044
Procirc 921 Microetch	923001
Procirc 923 Microetch	927001
Procirc SP263 Microetch	923003

Whilst every endeavour has been made to ensure that the information given in this Data Sheet is correct, PMD (UK) Limited gives no warranty, express or implied, relating to the use or performance of this product.