

# **MFS 1308**

## **COPPER ETCH/CLEANER**

### **INTRODUCTION**

MFS 1308 Copper Etch/Cleaner is a copper cleaning solution used as a first step in producing a clean, micro-etched copper surface. It will clean, deoxidise, remove light oils and micro-etch bare copper P.C. boards, leaving a clean copper surface.

MFS 1308 Copper Etch/Cleaner is ideal for use prior to dry film lamination and hot air levelling.

### **BENEFITS**

Economical micro-etch with ideal surface roughness.

Simple maintenance for controlled performance.

Rinses easily and completely for a truly clean surface.

May be used in immersion or spray application.

### **SOLUTION MAKE-UP**

MFS 1308 Copper Etch/Cleaner

10-100% v/v with water

### **OPERATING DATA**

Concentration	10-100%
Temperature	20-50°C
Time	1-3 minutes
Etch rate	0.1-1.0µm/min
Extraction	Recommended

**MFS1308-03/03**  
**ISSUE 3**

**EQUIPMENT**

Tanks	Polypropylene or polyethylene.
Heaters	Teflon, PTFE with thermostatic control.

**INSTALLATION**

It is essential that tanks to be used for MFS 1308 Copper Etch/Cleaner are cleaned and leached thoroughly before any product is added

Contact PMD (UK) Limited Technical Department for appropriate procedure.

1. Fill tank with appropriate amount of water.
2. Add the required volume of MFS 1308 Copper Etch/Cleaner.
3. Make-up to the operating volume with water.
4. Heat to operating temperature.

**PROCESS SEQUENCE**

1. MFS 1308 Copper Etch/Cleaner.
2. Rinse.
3. Rinse.
4. Continue depending on process.

**MAINTENANCE AND CONTROL**

Replace drag out losses with fresh MFS 1308 Copper Etch/Cleaner at the relevant concentration.

---

**DISPOSAL**

Dispose of in accordance with Local Authority requirements.

---

**PRODUCT FAMILIES**

The following products are referred to in this Data Sheet.

<u>Product Name</u>	<u>Product Number</u>
MFS 1308 Copper Etch/Cleaner	917030

---

Whilst every endeavour has been made to ensure that the information given in this Data Sheet is correct, PMD (UK) Limited gives no warranty, express or implied, relating to the use or performance of this product.